

SINGLE FREQUENCY INFRARED

X9800 Model Matrix

MODEL	DESCRIPTION	
X9800	Single Frequency IR Flame Detector	
	TYPE	MATERIAL
	A	Aluminum
	S	Stainless Steel (316)
	TYPE	THREAD TYPE
	3M	3 Port, Metric M25
	3N	3 Port, 3/4" NPT
	4M	4 Port, Metric M25
	4N	4 Port, 3/4" NPT
	TYPE	OUTPUTS
	11	Relay
	13	Relay and 4-20 mA
	14	Eagle Quantum Premier
	15	Relay and Pulse
	16	Addressable Module Only (third-party type)
	33	Relay and 4-20 mA / NTSC (xWatch)
	34	Eagle Quantum Premier / NTSC (xWatch)
	43	Relay and 4-20 mA / PAL (xWatch)
	44	Eagle Quantum Premier / PAL (xWatch)
	TYPE	APPROVAL AGENCY
	W	FM/CSA/CENELEC/CE
	A	FM/CSA
	R	VNIIPO/VNIIFTRI (RUSSIA)
	U	TCCEXEE/UKRCEPRO (UKRAINE)
	Y	CCCF (CHINA)
	TYPE	CLASSIFICATION*
	1	Division/Zone Ex de
	2	Division/Zone Ex d

*Detectors are always Class I, Div. I. See Manual