## **Sounder RF** FI700/RF/WM/SOUx

- Bi-directional digital communication with RF Interface FI700/RF/W2W
- 3 tone types selectable
- Sound level adjustable
- High range of radio transmission - up to 3km
- Long battery life 5 years
- Base and batteries included



## **Description**

The red Radio Sounder FI700/RF/WM/SOUR and the white Radio Sounder FI700/RF/WM/SOUW communicate with the fire detection control panel via a loop RF Interface FI700/RF/W2W or a conventional RF Interface FI700/RF/CWE. The radio sounders are especially suitable for areas where cabling is impossible or uneco-

DIL switch. The following tones are available:

- Slow whoop tone according to NEN 2575,
- Emergency signal according to DIN 33404,
- Continuous tone 990Hz.

The sound level can also be adjusted.

During the learning phase, the address is set in the range 2 to 240 by means of the configuration software WirelEx.

The sounders are integrated in a plastic housing and are designed for indoor wall mounting. Two batteries are accommodated inside the base. Normally, the soun-The tone type of the sounders can be selected with a ders are powered by the main battery. However, if the main battery fails, the secondary battery powers the

> The base, a special tool for opening the case and the batteries are included with the sounders.

## **Specifications**

Operating voltage	2 lithium batteries 3V, type CR123
Battery life	approx. 5 years (main battery) approx. 2 months (secondary battery, after failure of main battery)
Range of radio transmission (free air)	max. 200m max. 3km with expanders
Frequency band	868MHz
Sound level	100dB(A) at 1m distance
Ambient temperature	-10°C to +55°C
Protection class	IP21
Dimensions $\emptyset \times D$	106 × 95 (mm)
Weight	200g (without batteries)
·	





KF sounder red	
Approvals	LPCB 928q/05 0832-CPD-1688
Order number	355181
Order name	Sounder/700/RF/Red FI700/RF/WM/SOUR
RF sounder white	
Approvals	LPCB 928q/08 0832-CPD-1688
Order number	355195
Order name	Sounder/700/RF/White FI700/RF/WM/SOUW



## **ASTEC** B.V.

Kerkweg 70 6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77 Fax: +31 (0)46 443 04 82 E-mail: <u>info@astec.nl</u> Internet: <u>www.astec.nl</u>

Building Safety. Building Security.

