Product data sheet

SmartCell

SC-23-0220-0001-99

SmartCell Dual Smoke/Heat Detector and Combined Sounder-Beacon (VAD White Flash)

Overview

The SmartCell Dual Smoke / Heat Detector With Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, integrated sounder with 32 tones, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Includes part 23 beacon
- Unique design
- Inbuilt locking mechanism

SC-23-0220-0001-99

SmartCell Dual Smoke/Heat Detector and Combined Sounder-Beacon (VAD White Flash)

Technical specifications

Sounder	
Output level	93 dB(A) at 1 m max.
Selectable tones	32
Output level adjustment	: High or low
VAD	
Colour	White
Rating	C-3-12
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
General	
Wireless frequency	868 MHz
Compatibility	SmartCell
Physical	
Physical dimensions	110 x 58 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Ceiling mount
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C
Standards & regula	ation
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-5
	EN54-7
	EN54-13
	EN54-23 EN54-25
Detection	
Sensitivity	Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS),
	72 °C rate of rise (BR)



Kerkweg 70 6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77 Fax: +31 (0)46 443 04 82

E-mail: info@astec.nl Internet: www.astec.nl