

# SC-51-0100-0001-99

## SmartCell Fire Manual Call Point

### Overview

---

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

---

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

# SC-51-0100-0001-99

## SmartCell Fire Manual Call Point

### Technical specifications

---

#### General

Status indication	LED
Wireless frequency	868 MHz
Compatibility	SmartCell

#### Physical

Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount
Batteries	2 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)

#### Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor

#### Standards & regulation

Compliance	CE
Certification	CPR
Standards	EN54-13 EN54-25

**ASTEC**<sub>B.V.</sub>

Kerkweg 70  
6155 KN Puth (NL)  
Tel.: +31 (0)46 443 55 77  
Fax: +31 (0)46 443 04 82  
E-mail: [info@astec.nl](mailto:info@astec.nl)  
Internet: [www.astec.nl](http://www.astec.nl)