

# SC-31-0100-0001-99

## SmartCell Red Sounder

### Overview

---

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

---

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-31-0100-0001-99

## SmartCell Red Sounder

### Technical specifications

---

#### Sounder

Output level	95 dB(A) at 1 m max.
Selectable tones	32
Output level adjustment	High or low

---

#### General

Wireless frequency	868 MHz
--------------------	---------

---

#### Physical

Physical dimensions	110 x 72 mm (Ø x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount
Mounting position	Wall
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)

---

#### Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C

---

#### Standards & regulation

Compliance	CE
Certification	CPR
Standards	EN54-3 EN54-13 EN54-25

---

**ASTEC** B.V.

Kerkweg 70

6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77

Fax: +31 (0)46 443 04 82

E-mail: [info@astec.nl](mailto:info@astec.nl)

Internet: [www.astec.nl](http://www.astec.nl)