

SC-31-0200-0001-99

SmartCell White Sounder

Overview

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-31-0200-0001-99

SmartCell White Sounder

Technical specifications

Sounder

Output level	95 dB(A) at 1 m max.
Selectable tones	32
Output level adjustment	High or low

General

Wireless frequency	868 MHz
--------------------	---------

Physical

Physical dimensions	110 x 72 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount
Mounting position	Wall
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C

Standards & regulation

Compliance	CE
Certification	CPR
Standards	EN54-3 EN54-13 EN54-25

ASTEC B.V.

Kerkweg 70

6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77

Fax: +31 (0)46 443 04 82

E-mail: info@astec.nl

Internet: www.astec.nl