

# SC-33-0120-0001-99

## SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)

### Overview

---

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

---

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-33-0120-0001-99

## SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)

### Technical specifications

---

#### Sounder

---

Output level 92 dB(A) at 1 m max.

Selectable tones 32

Output level adjustment High or low

---

#### VAD

---

Colour white flash

Rating C-3-12

Flash frequency 0.5 Hz (1 flash, every 2 seconds)

---

#### General

---

Wireless frequency 868 MHz

---

#### Physical

---

Physical dimensions 110 x 79 mm (Ø x D)

Net weight 0.2 kg

Colour Red

Mounting type Ceiling mount

Mounting position Ceiling

Batteries 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)

---

#### Environmental

---

Operating temperature -10 to +55°C

Storage temperature -10 to +30°C (with batteries)  
-10 to +55°C (without batteries)

Relative humidity 95% noncondensing max.

Environment Indoor

IP rating IP21C

---

#### Standards & regulation

---

Compliance CE

Certification CPR

Standards EN54-3  
EN54-13  
EN54-23  
EN54-25

---

# **ASTEC**<sub>B.V.</sub>

Kerkweg 70

6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77

Fax: +31 (0)46 443 04 82

E-mail: [info@astec.nl](mailto:info@astec.nl)

Internet: [www.astec.nl](http://www.astec.nl)