

SC-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-32-0220-0001-99

SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

Sounder

Output level 95 dB(A) at 1 m max.

Selectable tones 32

Output level adjustment High or low

VAD

Colour white flash

Rating W-2.4-6

Flash frequency 0.5 Hz (1 flash, every 2 seconds)

General

Wireless frequency 868 MHz

Physical

Physical dimensions 110 x 77 mm (Ø x D)

Net weight 0.2 kg

Colour White

Mounting type Wall mount

Mounting position Wall

Batteries 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or HCB)

Environmental

Operating temperature -10 to +55°C

Storage temperature -10 to +30°C (with batteries)
-10 to +55°C (without batteries)

Relative humidity 95% noncondensing max.

Environment Indoor

IP rating IP21C

Standards & regulation

Compliance CE

Certification CPR

Standards EN54-3
EN54-13
EN54-23
EN54-25

ASTEC_{B.V.}

Kerkweg 70

6155 KN Puth (NL)

Tel.: +31 (0)46 443 55 77

Fax: +31 (0)46 443 04 82

E-mail: info@astec.nl

Internet: www.astec.nl