


RF Remote Indicator FI750/RF/PA



- **Bi-directional communication with RF Interface Series FI750/RF**
- **Remote indication of the activation of one or multiple wireless detectors**
- **Bright, power-saving LED**
- **Long battery life – up to 10 years**
- **Easy programming through „Scan and Link Option“**
- **Redundant radio connection with range of up to 500m**



Description

The RF Remote Indicator FI750/RF/PA is used for the remote display of the alarm activation of a fire detector in the fire detection system FI750/RF. In this way, an activated detector can be located quickly if the status LED on the detector is not visible or if the indicator is placed at a remote site.

That is necessary, for example, if the detector is installed in a false ceiling or false floor, or if the activation of a detector in a hotel room is to be indicated in the corridor.

The remote indicator communicates with the fire detection control panel via a loop RF Interface FI750/RF/W2W or a conventional RF Interface FI750/RF/CWE.

Depending on the parameterisation, the remote indicator can indicate the activation of an individual detector, or several detectors – for example those belonging to

a detection area – can be combined for a common display.

For the bi-directional data transmission, 66 data channels in the 868MHz frequency band are available. During the learning phase, the address is set in the range 2 to 240 by means of the PC software TauREX.

Two batteries which are inserted into the remote indicator provide power. The batteries are included.

The RF Remote Indicator FI750/RF/PA is integrated into a white plastic case and is designed for indoor installation.

The RF system is especially suitable for areas where cabling is impossible or uneconomical.


Specifications

Power supply	2 lithium batteries CR123A
Battery life	up to 10 years
Range of radio transmission (free air)	max. 500m
Frequency band	868 MHz
Ambient temperature	-10°C to 55°C
Relative humidity	95%

Building Safety. Building Security.

LST

Protection class	IP42
Dimensions W × H × D	80 × 80 × 32 mm
Colour	white
Weight	60g
Order number	251023
Order name	Remote Indicator/750/RF FI750/RF/PA



Building Safety. Building Security.

